





**Double Diode Module  
For Phase Control  
MDx-215-22-F**

Electrically isolated base plate  
Industrial standard package  
Simplified mechanical design, rapid assembly  
Pressure contact

Average forward current	$I_{FAV}$	215 A
Repetitive peak reverse voltage	$V_{RRM}$	2000 ÷ 2200 V
$V_{RRM}$ , V	2000	2200
Voltage code	20	22
$T_j$ , °C	- 40 ÷ 150	



All dimensions in millimeters (inches)


## MAXIMUM ALLOWABLE RATINGS

Symbols and parameters		Units	Values	Test conditions
<b>ON-STATE</b>				
$I_{FAV}$	Average forward current	A	215	$T_c = 100\text{ }^\circ\text{C}$ ; 180° half-sine wave; 50 Hz
$I_{FRMS}$	RMS forward current	A	337	
$I_{FSM}$	Surge forward current	kA	6.4 7.5	$T_j = T_{j\max}$ $T_j = 25\text{ }^\circ\text{C}$ 180° half-sine wave; 50 Hz ( $t_p = 10\text{ ms}$ ); single pulse; $V_R = 0\text{ V}$ ;
			7.0 8.1	$T_j = T_{j\max}$ $T_j = 25\text{ }^\circ\text{C}$ 180° half-sine wave; 60 Hz ( $t_p = 8.3\text{ ms}$ ); single pulse; $V_R = 0\text{ V}$ ;
$I^2t$	Safety factor	$A^2s \cdot 10^3$	205 270	$T_j = T_{j\max}$ $T_j = 25\text{ }^\circ\text{C}$ 180° half-sine wave; 50 Hz ( $t_p = 10\text{ ms}$ ); single pulse; $V_R = 0\text{ V}$ ;
			185 245	$T_j = T_{j\max}$ $T_j = 25\text{ }^\circ\text{C}$ 180° half-sine wave; 60 Hz ( $t_p = 8.3\text{ ms}$ ); single pulse; $V_R = 0\text{ V}$ ;
<b>BLOCKING</b>				
$V_{RRM}$	Repetitive peak reverse voltages	V	2000÷2200	$T_{j\min} < T_j < T_{j\max}$ ; 180° half-sine wave; 50 Hz;
$V_{RSM}$	Non-repetitive peak reverse voltages	V	2100÷2300	$T_{j\min} < T_j < T_{j\max}$ ; 180° half-sine wave; 50 Hz; single pulse;
$V_R$	Reverse continuous voltages	V	$0.75 \cdot V_{RRM}$	$T_j = T_{j\max}$ ;
<b>THERMAL</b>				
$T_{stg}$	Storage temperature	$^\circ\text{C}$	- 40 ÷ 125	
$T_j$	Operating junction temperature	$^\circ\text{C}$	- 40 ÷ 150	
<b>MECHANICAL</b>				
a	Acceleration under vibration	$\text{m/s}^2$	50	


## CHARACTERISTICS

Symbols and parameters		Units	Values	Conditions
<b>ON-STATE</b>				
$V_{FM}$	Peak forward voltage, max	V	1.40	$T_j = 25\text{ }^\circ\text{C}$ ; $I_{FM} = 500\text{ A}$
$V_{F(TO)}$	Forward threshold voltage, max	V	0.80	$T_j = T_{j\max}$ ; $0.5 \pi I_{FAV} < I_T < 1.5 \pi I_{FAV}$
$r_T$	Forward slope resistance, max	$\text{m}\Omega$	0.920	
<b>BLOCKING</b>				
$I_{RRM}$	Repetitive peak reverse current, max	mA	20	$T_j = T_{j\max}$ ; $V_R = V_{RRM}$
<b>SWITCHING</b>				
$Q_{rr}$	Total recovered charge, max	$\mu\text{C}$	810	$T_j = T_{j\max}$ ; $I_{FM} = 200\text{ A}$ ; $di_R/dt = -10\text{ A}/\mu\text{s}$ ; $V_R = 100\text{ V}$ ;
$t_{rr}$	Reverse recovery time, max	$\mu\text{s}$	17	
$I_{rrM}$	Peak reverse recovery current, max	A	95	
<b>THERMAL</b>				
$R_{thjc}$	Thermal resistance, junction to case			180° half-sine wave, 50 Hz
	per module	$^\circ\text{C}/\text{W}$	0.0900	
	per arm	$^\circ\text{C}/\text{W}$	0.1800	
	per module	$^\circ\text{C}/\text{W}$	0.0850	
$R_{thch}$	Thermal resistance, case to heatsink			DC
	per module	$^\circ\text{C}/\text{W}$	0.0300	
	per arm	$^\circ\text{C}/\text{W}$	0.0600	
	per module	$^\circ\text{C}/\text{W}$	0.0300	

<b>INSULATION</b>					
V <sub>ISOL</sub>	Insulation test voltage	kV	3.00	Sine wave, 50 Hz; RMS	t=1 min
			3.60		t=1 sec
<b>MECHANICAL</b>					
M <sub>1</sub>	Mounting torque (M6) <sup>1)</sup>	Nm	6.00	Tolerance ± 15%	
M <sub>2</sub>	Terminal connection torque (M6) <sup>1)</sup>	Nm	6.00	Tolerance ± 15%	
w	Weight	g	320		

<b>PART NUMBERING GUIDE</b>						<b>NOTES</b>					
MD	3	-	215	-	22	-	F	-	N		1) The screws must be lubricated
1	2		3		4		5		6		
1. MD - Rectifier Diode 2. Circuit Schematic 3. Average Forward Current, A 4. Voltage Code 5. Package Type (M.F) 6. Ambient Conditions: N – Normal											
		UL certified file-No. E255404									

The information contained herein is confidential and protected by Copyright.  
 In the interest of product improvement, Proton-Electrotex reserves the right to change data sheet without notice.




**Fig 1 – On-state characteristics of Limit device**

Analytical function for On-state characteristic:

$$V_F = A + B \cdot i_F + C \cdot \ln(i_F + 1) + D \cdot \sqrt{i_F}$$

	Coefficients for max curves	
	$T_j = 25^\circ\text{C}$	$T_j = T_{j\text{max}}$
<b>A</b>	0.928866	0.652364
<b>B</b>	0.673471	0.843733
<b>C</b>	-0.280459	-0.398101
<b>D</b>	0.352656	0.500582

**On-state characteristic model (see Fig. 1)**



**Fig 2 – Transient thermal impedance**

Analytical function for Transient thermal impedance junction to case  $Z_{thjc}$  for DC:

$$Z_{thjc} = \sum_{i=1}^n R_i \left( 1 - e^{-\frac{t}{\tau_i}} \right)$$

Where  $i = 1$  to  $n$ ,  $n$  is the number of terms in the series.

$t$  = Duration of heating pulse in seconds.


$Z_{thjc}$  = Thermal resistance at time  $t$ .

$R_i$  = Amplitude of  $p_{th}$  term.


$\tau_i$  = Time constant of  $r_{th}$  term.

$i$	1	2	3	4	5	6
$R_i$ K/W	0.0007653	0.00703	0.01629	0.04126	0.01513	0.09951
$\tau_i$ S	0.0002111	0.002366	0.06905	0.1909	0.6646	6.64


**Transient thermal impedance junction to case  $Z_{thjc}$  model (see Fig. 2)**




**Fig 3 – Total recovered charge,  $Q_{rr-i}$  (integral)**




**Fig 4 - Recovered charge,  $Q_{rr}$  (linear)**




**Fig 5 – Peak reverse recovery current,  $I_{fm}$**



**Fig 6 – Maximum recovery time,  $t_{tr}$  (linear)**




**Fig 7 – On-state power loss (sinusoidal current waveforms)**




**Fig 8 – On-state power loss (rectangular current waveforms)**







**Fig 9 – Maximum case temperature DSC (sinusoidal current waveforms)**



**Fig 10 – Maximum case temperature DSC (rectangular current waveforms)**



**Fig 11 – Maximum surge and  $I^2t$  ratings**



**Fig 12 – Maximum surge ratings**